

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition
1	IS&R	L1	6286	(385/31,49,14,36).CCLS.	US-PGPUB; USPAT	2007/0 3/01 18:04		
2	BRS	L2	5372	(mirror or mirrored or reflector or reflective or deflector) with ("45" or "54.7" or "54.74" or "70.5" or "70.53") with (degree or degrees)	US-PGPUB; USPAT	2007/0 3/01 18:04		
3	BRS	L3	155	L1 and L2	US-PGPUB; USPAT	2007/0 3/01 18:04		
4	BRS	L4	47	L2 same (pyramid or pyramidal)	US-PGPUB; USPAT	2007/0 3/01 18:04		
5	BRS	L5	193	L2 same (fiber or waveguide) same (pd or photodiode or photodetector or ld or laser or vcsl)	US-PGPUB; USPAT	2007/0 3/01 18:04		
6	BRS	L6	216	((mirror or mirrored or reflector or reflective or deflector) with (pyramid or pyramidal or triangular)) and "385"/\$.ccls.	US-PGPUB; USPAT	2007/0 3/01 18:04		
7	BRS	L7	2431	(mirror or mirrored or reflector or reflective or reflected or reflects or deflector) with (cantilever or cantilevered or ((bridge or suspended) adj2 waveguide))	US-PGPUB; USPAT	2007/0 3/01 18:04		
8	BRS	L8	173	L7 and "385"/\$.ccls.	US-PGPUB; USPAT	2007/0 3/01 18:04		
9	BRS	L9	728	L3 or L4 or L5 or L6 or L8	US-PGPUB; USPAT	2007/0 3/01 18:04		

10 / 681019 (update)

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition
10	BRS	L10	38	L9 and @pd>"20060917"	US-PGPUB; USPAT	2007/03/01 18:04		

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition
1	BRS	L2	33	(mirror and ("45" or "54.7" or "54.74" or "70.6" or "70.52") and layer and (resin or cantilever) and (filled or concave or solid)).clm.	US-PGPUB	2007/03/01 18:44		

(interf.)